



Main facts

- Flush installation
- Water tank
- Hot air 30 °C to 230 °C can be combined with chosen humidity level of 0%, 30%, 60%, 80% or 100%
- TFT touch display
- Panel-free appliance with surface control module
- Steaming without pressure
- Electronic temperature control from 30 °C to 230 °C
- Core temperature probe, removable
- Net volume 42 litres
- Energy efficiency class A

Heating methods

- Hot air + 100 % humidity.
- Hot air + 80 % humidity.
- Hot air + 60 % humidity.
- Hot air + 30 % humidity.
- Hot air + 0 % humidity.
- Dough proofing.
- Defrosting.
- Regenerating.
- Low temperature cooking.

Handling

- Rotary knob and TFT touch display operation.
- Clear text display in 25 languages.
- Option to save individual recipes (incl. core temperature probe).
- Information key with use indicators.
- Side-opening door opens up to 110° angle.

Features

- Removable 1.3 litre water tank.
- Water level warning.
- Core temperature probe with automatic shut-off.
- Actual temperature display.
- Timer functions: cooking time, cooking time end, timer, stopwatch, long-term timer.
- Electronic boiling point detection.
- 48 W halogen light on the side.
- Hygienic stainless steel cooking interior.
- 4 tray levels.

Safety

- Child lock.
- Safety shut-off.
- Cooled housing with temperature protection.

Cleaning

- Cleaning aid.
- Drying programme.
- Descaling programme.
- Grease filter, dishwasher-safe.

Connection

- Energy efficiency class A.
- Total connected load 2.0 kW.
- Connection cable 1.5 m without plug.