熱水爐系列 Water Heater Series 用氣量:千瓦(千克/小時) 型號 顏色代號# 整體尺寸:高x闊x深(毫米/吋) 熱水供應量:(公升/分鐘) 電源供應 Gas Consumption: kW (kg/hr) Model Overall Dimensions: H x W x D (mm/inch) Colour Code Hot Water Supply: (litre/min.) **Electricity Supply** 最高 Maximum 最低 Minimum RRJW150SFD 584 x 350 x 70 / 23.0 x 13.8 x 2.8 33.7 (2.42) 8.1 (0.58) RJW120RFL+ 26.7 (1.93) 6.7 (0.49) 675 x 370 x 128 / 26.6 x 14.6 x 5.0 RJW160RFL+ 35.0 (2.54) 8.6 (0.62) 交流電220伏特 (50赫) RSW150RFL / RSW150TFL 33.7 (2.44) 4.4 (0.32) 220V a.c. 675 x 370 x 130 / 26.6 x 14.6 x 5.1 RSW120RFL / RSW120TFL 27.3 (1.98) 4.4 (0.32) (50Hz)

26.7 (1.93)

21.5 (1.56)

6.5 (0.47)

4.1 (0.30)

565 x 330 x 132 / 22.2 x 13.0 x 5.2 所有型號採用機動排氣密封式設計。Fan Assisted Room-sealed design applies to all models. * †相應的氣體應用指南之五(GU05)型號:TRJW120RFL 和 TRJW160RFL。Corresponding Code of Practice GU05 Model:TRJW120RFL and TRJW160RFL.

675 x 370 x 135 / 26.6 x 14.6 x 5.3

嵌入式平面爐系列 Built-in Hob Series

RSW110RF/RSW111TF

RSW10RF / RSW10TF

▲ 爐底至廚櫃面 From Bottom To Bench Top

型號 Model	顏色代號 # Colour Code	▲ 整體尺寸:高 x 関 x 深 (毫米/吋) Overall Dimensions : H x W x D (mm/inch)	最高用氣量 : 千瓦 (千克/小時) Maximum Gas Consumption : kW (kg/hr)			櫃面開孔尺寸:闊 x 深 (毫米/吋)	電源供應	
			左殟垻	中爐頭 Middle Burner	右爐頭 Right Burner	Cut-out Dimensions : W x D (mm/inch)	Electricity Supply	
RRDB62S	HF	54 x 770 x 452 / 2.1 x 30.3 x 17.8	4.6 (0.33)		4.6 (0.33)	670 x 350 / 26.4 x 13.8 703 x 403 / 27.7 x 15.9	"C" 型電池 1.5伏特 x 1 "C" Size Battery 1.5V x 1	
RRTB62S-G-LP	BG, WG	56 x 720 x 420 / 2.2 x 28.3 x 16.5	4.6 (0.33)	-	4.6 (0.33)	670 x 350 / 26.4 x 13.8		
RRTB83S-G-LP	BG	56 x 860 x 450 / 2.2 x 33.9 x 17.7	4.6 (0.33)	2.6 (0.19)	4.6 (0.33)	815 x 405 / 32.1 x 15.9		

座檯式煮食爐系列 Hotplate Series

爐底至爐面 From Bottom To Top Plate

型號 Model	顏色代號 #	●整體尺寸:高×闊×深 (毫米/吋)	最高用氣量 : 千瓦 (千克/小時) Maximum Gas Consumption : kW (kg/hr)			電源供應	
	Colour Code	Overall Dimensions : H x W x D (mm/inch)	左爐 頭 Left Burner	中置煮飯爐頭 Centre Rice Burner	右爐頭 Right Burner	Electricity Supply	
R3HR		180 x 692 x 420 / 7.1 x 27.2 x 16.5	6.0 (0.43)	1.2 (0.09)	6.0 (0.43)		
R22	SSW	180 x 662 x 420 / 7.1 x 26.1 x 16.5	5.5 (0.40)	-	5.5 (0.40)	"C"型電池 1.5伏特 x 1 "C" Size Battery 1.5V x 1	
RRJH2		180 x 692 x 452 / 7.1 x 27.2 x 17.8	6.0 (0.43)	-	6.0 (0.43)		
RRSH2	SS	120 717 207 / F 1 20 2 15 2	5.0 (0.36)	-	5.0 (0.36)	-	
RRJH21	HF	129 x 717 x 387 / 5.1 x 28.2 x 15.2	4.3 (0.31)	-	4.3 (0.31)	"C" 型電池 1.5伏特 x 1 "C" Size Battery 1.5V x 1	
R1N	SS	129 x 277 x 387 / 5.1 x 10.9 x 15.2	-	4.3 (0.31)	-		

BG: 黑色玻璃 Black Glass WG: 白色玻璃 White Glass WE: 白色搪瓷 White Enamel SS: 不銹鋼 Stainless Steel SSW: 不銹鋼面 + 白色爐身 Stainless Steel Surface + White Body HF: 拉絲面不銹鋼 Stainless Steel of Hairline Finish



所有林內石油氣爐皆獲 機電工程署氣體安全監督批准

All Rinnai LPG Appliances are approved by Gas Authority of Electrical and Mechanical Services Department

價格及規格如有更改, 恕不另行通知。

All prices and specifications are subject to change without notice.

總 代 理 : 香港中華煤氣有限公司

Sole Agent: The Hong Kong and China Gas Company Limited

電話 Tel: 2232 1111

- © 版權所有。未獲本公司授權,不得翻印、複製或使用本單張作任何用途。
- © All rights reserved. Copying, reproducing or using the contents of this leaflet are not allowed without prior permission from Towngas.
- * 免費維修保養的服務只適用於住宅用戶,而在馬灣、大嶼山(東涌除外)及離島提供 維修保養服務須收取附加費。所有行使禁區紙的地區則不獲提供維修保養服務。

Free warranty servicing only for residential customers. For Ma Wan, Lantau Island (except Tung Chung), and outlying islands, surcharge will be applied. Warranty servicing will not be provided for all restricted areas.

保養服務並不包括損耗配件(如爐架、溢湯盤、爐蓋及爐環等)。

This warranty service does not cover consumable parts (e.g. pan support, drip pan, burner cap and burner ring).

新更換爐具零件(不包括損耗配件)的保養期延長至24個月。

Warranty of newly replaced spare parts (except consumable parts) is extended to 24 months.







林内 Rinnai

EXPERIENCE OUR INNOVATION

優質石油氣爐具

林內牌石油氣爐具系列 Rinnai LPG Appliance Series

> 特長3年包零件免費保養* 3-year warranty including parts

COOLER







林內牌石油氣爐具系列 Rinnai LPG Appliance Series



熱水爐系列 Water Heater Series

超薄型 Superslim Type



RRJW150SFD \$10,180

恆溫型 Temperature-modulated Type



RJW160RFL \$9,080





RSW150RFL \$6.980 RSW150TFL \$6.980

- 自動恆溫,確保水溫穩定 Automatic water temperature modulation
- 數碼式溫度控制系統,熱水由 37℃至60℃(共15級選擇) 15 digitally-controlled water temperature settings from 37°C to 60°C
- · 可選配2個數碼式電子遙控器, 同時安裝 在浴室及廚房,額外每個 \$600 2 optional bathroom and / or kitchen digital remote controls available at \$600 each



標準型 Standard Type



全自動打火,操作簡易 Automatic electronic ignition system

- 5段火力及水量調節掣, 滿足不同需要
- 5 flame levels and water volume settings to meet different needs

座檯式煮食爐系列 Hotplate Series





• 自動恆溫,確保水溫穩定

Automatic water temperature

浴室及廚房,額外每個 \$600

可選配2個數碼式電子遙控器,同時安裝在

2 optional bathroom and / or kitchen

digital remote controls available at

防漏安全裝置

內置煮飯煲,飯熟自動熄火 cooking function

lame Failure Device

特大火力爐頭,更夠鑊氣 Extra powerful flame for



- 按鍵式電子點火系統 Push button
- 易潔陶瓷銅合金爐頭環 brass burner cap





- 特大火力爐頭,更夠鑊氣 better cooking results
- 防止兒童開關安全鎖 Child safety lock

耐用銅合金爐頭環

Durable brass

▶ 壓電式打火裝置



- 特大火力爐頭,更夠鑊氣 better cooking results
- 防止兒童開關安全鎖 Child safety lock



- 按鍵式電子點火系統 Push button
- 易潔陶瓷銅合金爐頭環 Easy cleaning ceramion brass burner cap

嵌入式平面爐系列 Built-in Hob Series



拉絲面不銹鋼 Hairline Finish Stainless Steel Surface



全自動打火,操作簡易

• 自動恆溫,確保水溫穩定

modulation

to 55 ℃

Automatic electronic ignition

Automatic water temperature

• 數碼式溫度控制系統,熱水由

37℃至55℃(共14級選擇)

14 digitally-controlled water

- Fully sealed burner design avoids food spills into appliance ● 特設輔助承托架

• 全密封式爐頭設計,令食物汁液不易溢進爐內

- Special made auxiliary support
- 提供兩款開孔尺寸選擇 2 cut-out sizes available

強化玻璃面 Tempered Glass Surface







- 全密封式爐頭設計,令食物汁液不易溢進爐內 Fully sealed burner design avoids food spills into appliance
- 特大火力爐頭,配以獨立爐芯火 Extra powerful burner with simmer flame