

EFB90680BX

90cm Chimney Hood - Perimetrical aspiration for the best performance and easy cleaning integrated design



[Where to buy](#)

[Add to compare](#)

[Print this page](#)

[Send to a friend](#)

[Share this page](#)



[Jump to](#)

[Key features](#)

[Specifications](#)

[Support](#)

Key features for EFB90680BX - Cooking

[▲ Back to top](#)

Easy Cleaning

This cooker hood uses perimetral aspiration to whisk away odours with great efficiency.

A mild form of selecting the speed of extraction and light level

Electronic touch controls give you precise control to select the appropriate extraction rate. What's more, you can also use them to adjust the light level. [Read more](#)

Always know exactly when to change the filter

Thanks to this cooker hood's time-to-change indicator, you will always know exactly when to change the filter. That way, your hood is always super effective. [Read more](#)

Fresh air, low energy use, and low noise

Thanks to its professional InverterTechnology motor, this cooker hood does more than freshening up your kitchen; it also uses energy efficiently, and is super quiet. [Read more](#)

Clean the air in your kitchen without lifting a finger

Whatever you're cooking, this cooker hood ensures the air in your kitchen is always fresh. Its sensor technology detects vapours and switches the cooker hood on for you. [Read more](#)

This product comes with

3 aluminium cassette grease filter

White LED display with touch controls on glass

For circulation or extraction operation mode

IQ Touch with 5-fan speed and power boost

Made in Italy

Inverter technology

Perimetral Aspiration, the perfect smoke removal system

Power boost to maximum 1100 m³/h airflow, reducing clean-up time

Indicator for grease & carbon filter saturation

Inverter motor

Smoke and vapour sensor

Specifications for EFB90680BX - Cooking

[▲ Back to top](#)

Height (mm)	800-940	Total power of the lamps (W)	8	Control Settings	Touch	Connection (W)	278
Width (mm)	898	Total power of the motors (W)	270	Control type	Electronic	Maximum output air extraction (m ³ /h)	1,100
Depth (mm)	470	Voltage (v)	220-240	No-return airflow flap	Yes	Noise	67
Colour Body	Stainless Steel	Diameter of air outlet (mm)	150	Speed Settings	5	Operating Mode	Convertible
Colour Chimney	Stainless Steel	Grease Filter Type	Multilayer cassette	Lamp Type	Dimming LED	Number of Lights	4
Product Installation	Wall-mounted	Grease Filter Material	Washable aluminium	Boost	Yes		