



### Main facts

- Handleless door / automatic door opening
- Fixed inlet and outlet water connection
- Hot air 30 °C to 230 °C can be combined with chosen humidity level of 0%, 30%, 60%, 80% or 100%
- Full surface grill behind glass ceramic for easy cleaning, combinable with circulated air up to 230 °C and steam
- TFT touch display
- Panel-free appliance with surface control module
- Steaming without pressure
- Electronic temperature control from 30 °C to 230 °C
- Core temperature probe, removable
- Net volume 43 litres
- Energy efficiency class A

### Heating methods

Hot air + 100 % humidity.  
Hot air + 80 % humidity.  
Hot air + 60 % humidity.  
Hot air + 30 % humidity.  
Hot air + 0 % humidity.  
Full surface grill + circulated air.  
Full surface grill.  
Full surface grill level 1 + humidity.  
Full surface grill level 2 + humidity.  
Dough proofing.  
Defrosting.  
Regenerating.  
Low temperature cooking.

### Handling

- Automatic door opening.
- Rotary knob and TFT touch display operation.
- Clear text display in 25 languages.
- Option to save individual recipes (incl. core temperature probe).
- Information key with use indicators.
- Side-opening door opens up to 180° angle.

### Features

- Full surface grill 2000 W behind glass ceramic.
- Steam removal.
- Misting.
- Core temperature probe with automatic shut-off.
- Actual temperature display.
- Timer functions: cooking time, cooking time end, timer, stopwatch, long-term timer.
- Electronic boiling point detection.
- Capacity display for filter cartridge (if connected to GF 111 100 descaling system).
- 48 W halogen light on the side.
- Hygienic stainless steel cooking interior.
- 4 tray levels.

### Safety

- Child lock.
- Safety shut-off.
- Cooled housing with temperature protection.

### Cleaning

- Cleaning aid.
- Drying programme.
- Descaling aid.
- Grease filter, dishwasher-safe.

### Connection

- Energy efficiency class A.
- Total connected load 2.9 kW.
- Only cold water connection.
- Inlet hose 3.0 m with 3/4 " (26,4 mm) connection.
- Outlet hose (ø 25 mm) 3.0 m (HT-Hose).
- Plan a connection cable.