
































H 6890 BP

Construction type		^
Built-in wall oven	•	
Design		^
PureLine	•	
Colour	Stainless steel/Clean Steel	
Display	M Touch	
Convenience features		^
Precise temperature control	30 - 300°C	
Wireless food probe	• 	
Crisp function	• 	
Rotisserie	• 	
Operating modes		^
Defrost	• 	
Automatic programmes	More than 100	
Country-specific automatic programmes	•	
AutoRoast	• 	
Gentle bake	• 	
Economy grill	• 	
Fan plus	• 	
Intensive bake	• 	
Low temperature cooking	• 	
Moisture plus	• 	
Conventional heat	• 	
Top heat	• 	
Bottom heat	• 	
Fan grill	• 	
Special applications	• 	
User convenience		^
MyMiele	•	
Individual language selection	•	
3D control panel	• 	
Search function automatic programmes	•	
Timed steam bursts programmable	•	
Polyphonic audible signals	•	
Time of day display	• 	
Date display	•	
Minute minder	•	
Time buffer in h	200	
Start-stop programming	• 	
Automatic switch-off	•	
Programmable cooking time	• 	
Entry via number keypad	•	
Actual temperature display	•	
Recommended temperatures	•	
Audible signal when desired temperature is reached	•	
User programmes	20 	
Sabbath programme	•	
Individual settings	• 	
Door		^

CleanGlass door	•
Cavity ^	
Cavity volume in l	90
No. of rack levels	3
Labelling of rack levels	•
No. of halogen lamps	Four
TwinPower hot air fans	• 
Cleaning convenience ^	
Stainless steel front with CleanSteel surface	• 
Pyrolytic self-cleaning	•
Heated catalyser	• 
Tilt-down grill heater element	•
Efficiency and sustainability ^	
Energy efficiency classification	A
Energy-saving lighting circuit	•
Residual heat utilisation	• 
Rapid heat-up	• 
Safety ^	
Appliance cooling system with cool front	• 
Safety cut-out	• 
System lock	•
Door contact switch	•
Door lock during pyrolytic cleaning	•
Technical data ^	
Niche width in mm	860
Niche height in mm	517
Niche depth in mm	550
Weight in kg	74,0
Total connected load in kW	5,6
Frequenz in Hz	50
Voltage in V	230
Fuse rating in A	25
Number of phases	1
Standard accessories ^	
Universal baking tray with PerfectClean	2
Baking and roasting rack PyroFit	2 
FlexiClip fully telescopic runners PyroFit	2 pairs
Side racks PyroFit	1 pair 
Recipe booklet	•
Request card for recipe book	•
Connection cable	•
Descaling tablets	•